



2" LEG LENGTH

1/4" HOLES
PREDRILLED FOR
FASTENING TO WALL

ANCHOR FLOOR
PLATES

BACK UP PLATE
FOR HARDWARE

Special Note:

C-Channel frame wraps are not designed to independently support the door system. If used on IMP walls, the perimeter of the rough opening (full height and width) should be reinforced by others with wood or plastic lumber to support the frame and door system.

SPECIFICATIONS:

- WALL THICKNESS:
- WALL TYPE:
- FINISHED OPENING SIZE:

TO CALCULATE A ROUGH OPENING:

FINISHED WIDTH & ADD 1 1/4" =
FINISHED HEIGHT & ADD 5/8" =

MATERIAL TYPE

- 12 GA. PRIMED MILD STEEL (STANDARD)
- 12 GA. GALVANIZED (OPTIONAL)
- 12 GA. TYPE 430-#4 STAINLESS STEEL (OPTIONAL)

UNIT(S) REQUIRED:

ALL HOLES ARE PRE-DRILLED IN FRAME FOR QUICK AND EASY INSTALLATION.

DIMENSION "A" =

DIMENSION "B" =

DOOR MODEL #

MISC. NOTES:

MODEL # 12 GA. C-CHANNEL JAMB WRAP



ELIASON®

PH: 800-828-3655
FX: 800-828-3577

www.eliasoncorp.com

CUSTOMER INFORMATION:

DATE: 5/5/2006

APPROVAL

FORM # SD4590

REV. C